

**Applications**

 Agriculture  
 Forestry

Landscaping

**Main features**

Bi-directional rotation allows both top-cutting and undercutting in either travel direction.  
 Offset mounting permits tilling next to sidewalks, curbs and buildings.  
 Hydraulically-powered; no shear pins to maintain.  
 Able to use high-flow hydraulics for enhanced performance on 158 cm and 193 cm models.


Hardened, double-edge, replaceable tines.  
 Exclusive Bob-Tach™ mounting system permits quick hookup to loader.  
 Forward/reverse travel direction.

**Compatibility**

Description	Item number	Compatible with loader
Tiller 102 cm	7196028	T110-B, T110-E, MT55E, S70E, S100E
Tiller 158 cm	7104371	T450E IIIB, T590E IIIB, T590B iT4, T650E IIIB, T650E iT4, T650B iT4, S450E IIIA, S450B T2, S510E IIIA, S510B T2, S530E IIIA, S530B T2, S550E IIIB, S550B iT4, S570E IIIB, S570B iT4, S590E IIIB, S590B iT4, S630E IIIB, S630E iT4, S630B iT4, S650E IIIB, S650E iT4, S650B iT4, S770E IV, S770E T3, S770B T3

**Characteristics and Performance**

Description	Item number	Working width (mm)	Max. working depth (mm)	Number of tines	Required hydraulic flow (L/min)	Drive type
Tiller 102 cm	7196028	966.0	102.0	32	34.0-68.0	Chain
Tiller 158 cm	7104371	1575.0	152.0	36	64.0-140.0	Direct drive

**Weights and dimensions**


Description	Item number	Operating weight (kg)	Shipping weight (kg)	Overall Length (mm)	Overall Width (mm)	Overall Height (mm)
Tiller 102 cm	7196028	230.0	230.0	709.0	1020.0	793.0
Tiller 158 cm	7104371	321.0	321.0	836.0	1580.0	614.0